



**Ordering Information**

PM 254 - \* - N - \* - \* - \*\* - \*

No. of Rows 1=Single Row 2=Dual Row	No. of Pins 02-40Pin	Type 2-直插 3-弯插 4-弯插 5-弯插	Length (mm)	Contact Plating G0:Gold Flash G1:1u" Gold G2:3u" Gold G3:5u" Gold G4:10u" Gold G5:15u" Gold G6:30u" Gold S0:Gold Flash/Tin S1:Tin	Packing 默认=Tray (托盘) R=Reel +Cap (编带+盖) T=Tube (管脚)
---	-------------------------	--------------------------------------	----------------	--	--

			GENERAL TOLERANCE		制图 DRAWING		深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO., LTD			
			DIM	TOL	审核 CHECK					
			X.X	±0.30	批准 APPROVAL		产品名称 TITLE	2.54 单排 弯排母 塑高8.5	版本 REV.	A
1			初版发行		比例 SCALE		产品料号 PART NO.	PM254-1-N-W-8.5-XX(L10.2)	单位 UNITS	mm
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE	Angle	±3.0°	投影 Projection		材料 MATERIAL		页次 SHEET	1/1