



Recommended P.C.B Layout(Top Side)  
(PCB BOARD TOLERANCE $\pm 0.05$ )

SPECIFICATIONS  
 Rated Current:3.0AMP  
 Contact Resistance:20m $\Omega$ Max  
 Withstand Voltage:1000V AC/DC  
 Insulation Resistance:1000M $\Omega$ Min  
 Operation Temperature:-40 $^{\circ}$ c to +105 $^{\circ}$ c

Contact Material:Brass  
 Contact Plating:Au or Sn Over Ni  
 Insulator Material:Polyester(UL94V-0)  
 Resistance To Soldering Heat:  
 265 $^{\circ}$  C $\pm 5^{\circ}$  C, 10s(PA6T&PA9T&LCP insulator)

**Ordering Information**

PM 254 - \* - N - SE - \* - \*\*

No. of Rows 1=Single Row 2=Dual Row	No. of Pins 02-40Pin	Type Z-塑料 F-树脂 S-金属 WS-绝缘 WC-绝缘脚 DS-双侧贴片 SP-双侧插板	Length (Plastic) (英寸)	Contact Plating G0:Gold Flash G1:1u" Gold G2:3u" Gold G3:5u" Gold G4:10u" Gold G5:15u" Gold G6:30u" Gold
---	-------------------------	---	-----------------------------	---

		GENERL TOLERANCE		制图 DRAWING	深圳市华灿天禄电子有限公司 ShenzhenhuaciantianluELECTRONICS CO., LTD			
		DIM	TOL	审核 CHECK				
		X. X	$\pm 0.30$	批准 APPROVAL	产品名称 TITLE	2.54双排 双侧贴片 排母 塑高8.1	版本 REV.	A
		X. XX	$\pm 0.20$	比例 SCALE	产品料号 PART NO.	PM254-2-N-SE-8.1-XX(L11.1)	单位 UNITS	mm
		X. XXX	$\pm 0.10$	投影 Projection	材料 MATERIAL		页次 SHEET	1/1
1	初版发行	日期 MODIFY DATE	Angle	$\pm 3.0^{\circ}$				
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE	Angle	$\pm 3.0^{\circ}$				