



NOTES:
备注

1. Brass or purple copper, Bright tin-plating
黄铜或紫铜, 镀亮锡
2. Wire screw hole M4
压线螺孔M4
3. Current Rating: 60A
额定电流: 60A
4. There shall be no defects such as pin deformation and burrs.
不得有脚变形, 毛刺等缺陷
5. Unmarked dimensions refer to tolerances
未标注的尺寸参考公差

Ordering Information

HC - * ** * - **** - * ** * - 07

Type	Thickness	Screw Thread	Welding Feet	Series	Pin/P SERT	Product No.	Material
Pin (插脚)	0.8±0.05mm	0.8±0.05mm	0.8±0.05mm	1620±0.20mm	Pin	产品序号	镀锡铜 (黄铜)
Pin Nut (插脚螺母)	1.0±0.05mm	1.0±0.05mm	1.0±0.05mm	Pin	镀锡铜 (黄铜)
Pin Gasket (插脚垫片)	1.5±0.05mm	1.5±0.05mm	1.5±0.05mm	Pin	镀锡铜 (黄铜)
Pin Gasket (插脚垫片)	2.0±0.05mm	2.0±0.05mm	2.0±0.05mm	Pin	镀锡铜 (黄铜)
Pin Gasket (插脚垫片)	2.5±0.05mm	2.5±0.05mm	2.5±0.05mm	Pin	镀锡铜 (黄铜)
Pin Gasket (插脚垫片)	3.0±0.05mm	3.0±0.05mm	3.0±0.05mm	Pin	镀锡铜 (黄铜)

			GENEAL TOLERANCE	制图	07	深圳市华灿天禄电子有限公司 ShenzhenhuacantianlueLECTRONICS CO., LTD			
			DIM TOL	审核		产品名称	PCB 焊接端子 厚度1.0 插板 铆垫片	版本	A
			5 or more ±0.35	CHECK		TITLE	M4 4焊脚 10x8x11.2mm	REV.	
			2~5 ±0.25	批准		产品料号	HC-RG1044-1008-D312-07	单位	mm
			0~2 ±0.15	APPROVAL		PART NO.		页次	1/1
1	初版发行		Angle ±3.0°	比例		MATERIAL		SHEET	
序号	变更内容	日期	投影	Projection					
No.	MODIFY CONTENT	MODIFY DATE							