



NOTES:
备注

1. Brass or purple copper, Bright tin-plating
黄铜或紫铜, 镀亮锡
2. Wire screw hole M4
压线螺孔M4
3. Current Rating: 60A
额定电流: 60A
4. There shall be no defects such as pin deformation and burrs.
不得有脚变形, 毛刺等缺陷
5. Unmarked dimensions refer to tolerances
未标注的尺寸参考公差

Ordering Information

HC	-	*	**	*	-	****	-	*	***	*	-	07
Type Type (型号)	Thickness 厚度 (mm)	Screw 螺孔 (mm)	Thread 螺距 (mm)	Welding 焊脚 (mm)	Series 系列	Pin 脚数	Product No. 产品编号	Material 材料				
08x11.2mm	1.0mm	M4	0.8	1.0	0808x8x11.2mm	4	HC-RG1044-0808-D303-07	Bright Copper (亮铜)				

			GENERAL TOLERANCE	制图	07	深圳市华灿天禄电子有限公司 ShenzhenhuacuantianlueLECTRONICS CO., LTD			
			DIM TOL	审核		产品名称	PCB 焊接端子 厚度1.0 插板 铆垫片	版本	A
			5 or more ±0.35	批准		TITLE	M4 4焊脚 8x8x11.2mm	REV.	
			2~5 ±0.25	比例		产品料号	HC-RG1044-0808-D303-07	单位	mm
			0~2 ±0.15	投影		PART NO.		页次	1/1
序号	变更内容	日期	Angle ±3.0°	投影		MATERIAL		SHEET	
No.	MODIFY CONTENT	MODIFY DATE							