



NOTES:  
备注

1. Brass or purple copper, Bright tin-plating  
黄铜或紫铜, 镀亮锡
2. Wire screw hole M4  
压线螺孔M4
3. Current Rating: 60A  
额定电流: 60A
4. There shall be no defects such as pin deformation and burrs.  
不得有脚变形, 毛刺等缺陷
5. Unmarked dimensions refer to tolerances  
未标注的尺寸参考公差

**Ordering Information**

HC - \* \*\* \* - \*\*\*\* - \* \*\* \* - 07

Type	Thickness	Screw Thread	Welding Feet	Series	Pin/P	Product No.	Material
Pin1 Tooth (插牙)	0.5±0.1mm	0#03 (螺牙)	2#2个	08080808mm	Pin/P	产品序号	默认Copper (黄铜)
Pin1 Nut (螺螺母)	1.0±0.1mm	0#04 (螺牙)	2#2个	1620#16x20mm	Pin/P		Red Copper (紫铜)
Pin1 Gasket (螺垫片)	1.5±0.1mm	0#04 (螺牙)	4#4个	.....	Pin/P		
	2.0±0.2mm	0#06 (螺牙)	6#6个		Dip		
	2.5±0.2mm		8#8个				
	3.0±0.2mm						

		GENERAL TOLERANCE	制图	07		深圳市华灿天禄电子有限公司 ShenzhenhuacantianlueLECTRONICS CO., LTD			
		DIM TOL	审核			产品名称	PCB 焊接端子 厚度1.0 插板 铆垫片	版本	A
		5 or more ±0.35	批准			TITLE	M4 4焊脚 8x8x10.2mm	REV.	
		2~5 ±0.25	比例			产品料号	HC-RG1044-0808-D302-07	单位	mm
		0~2 ±0.15	投影			PART NO.		页次	1/1
序号	变更内容	日期	Projection			MATERIAL		SHEET	
No.	MODIFY CONTENT	MODIFY DATE							