



NOTES:

- 备注
- 1.Brass or purple copper,Bright tin-plating  
黄铜或紫铜, 镀亮锡
  - 2.Wire screw hole M5  
压线螺孔M5
  - 3.Current Rating: 100A  
额定电流:100A
  - 4.There shall be no defects such as pin deformation and burrs.  
不得有脚变形, 毛刺等缺陷
  - 5.Unmarked dimensions refer to tolerances  
未标注的尺寸参考公差

**Ordering Information**

HC - \* \* \* \* - \* \* \* \* - \* \* \* \* - 07

Type	Thickness	Screw Thread	Welding Feet	Series	Product No.	Material
① 插板 (插板)	① 1.5mm	① M5 (螺孔)	① 6脚	100	① 14.5x14.5x14mm	① 黄铜 (黄铜)
② 螺母 (螺母)	② 1.5mm	② M5 (螺孔)	② 6脚	100	② 14.5x14.5x14mm	② 紫铜 (紫铜)
③ 螺柱 (螺柱)	③ 1.5mm	③ M5 (螺孔)	③ 6脚	100	③ 14.5x14.5x14mm	③ 镀锡铜 (镀锡铜)
④ 螺柱 (螺柱)	④ 1.5mm	④ M5 (螺孔)	④ 6脚	100	④ 14.5x14.5x14mm	④ 镀锡铜 (镀锡铜)

		GENEAL TOLERANCE		制图	07		<b>深圳市华灿天禄电子有限公司</b> ShenzhenhuacantianluELECTRONICS CO., LTD			
		DIM	TOL	审核						
		5 or more	±0.35	批准			产品名称	PCB 焊接端子 厚度1.5 插板 铆垫片	版本	A
		2~5	±0.25	APPROVAL			TITLE	M5 6脚脚 14.5x14.5x14mm	REV.	
		0~2	±0.15	比例			产品料号	HC-RG1556-1414-D708-07	单位	mm
		Angle	±3.0°	SCALE			PART NO.		页次	1/1
序号	变更内容	日期	投影				MATERIAL		SHEET	
No.	MODIFY CONTENT	MODIFY DATE								