



NOTES:

备注

1. Brass or purple copper, tin-plating
黄铜或紫铜，镀锡
2. Wire screw hole M4
压线螺孔M4
3. Current Rating: 60A
额定电流:60A
4. There shall be no defects such as pin deformation and burrs.
不得有脚变形，毛刺等缺陷
5. Unmarked dimensions refer to tolerances
未标注的尺寸参考公差

Ordering Information

HC - * ** * - **** - * ** * - 07

Type	Thickness	Screw Thread	Welding Feet	Series	Pin/Pin	Product No.	Material
Pin (插针)	0.8±0.05mm	M3 (螺牙)	2mm	1620#16x20mm	Pin		Brass (黄铜)
Nut (螺母)	1.0±0.05mm	M4 (螺牙)	2mm	Pin		Brass (黄铜)
Washer (垫圈)	1.5±0.05mm	M3 (螺牙)	4mm				Brass (黄铜)
Gasket (垫片)	2.0±0.05mm	M3 (螺牙)	6mm				Brass (黄铜)
	2.5±0.05mm	M4 (螺牙)	8mm				Brass (黄铜)
	3.0±0.05mm	M4 (螺牙)				Brass (黄铜)

PCB 参考安装方式

		GENREL TOLERANCE		制图	07		深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO.,LTD			
		DIM	TOL	审核			产品名称	PCB 焊接端子 厚度1.0 插板 铆垫片	版本	A
		5 or more	±0.35	批准			TITLE	M4 4焊脚 10x8x11.2mm	REV.	
1	初版发行	2~5	±0.25	比例			产品料号	HC-RG1044-1008-D307-07	单位	mm
序号	变更内容	0~2	±0.15	投影			PART NO.		页次	1/1
No.	MODIFY CONTENT	Angle	±3.0°	Projection			MATERIAL		SHEET	