



NOTES:

- 备注
1. Brass or purple copper, Bright tin-plating
黄铜或紫铜, 镀亮锡
 2. Wire screw hole M5
压线螺孔M5
 3. Current Rating: 100A
额定电流: 100A
 4. There shall be no defects such as pin deformation and burrs.
不得有脚变形, 毛刺等缺陷
 5. Unmarked dimensions refer to tolerances
未标注的尺寸参考公差

Ordering Information

HC - * * * * - * * * * - * * * * - 07

Type	Thickness	Screw Thread	Welding Feet	Series	Product No.	Material
(镀锌)	(mm)	(螺孔)	(焊脚)	100mmx20mm	(产品号)	(黄铜)
(镀镍)	(mm)	(螺孔)	(焊脚)	100mmx20mm	(产品号)	(紫铜)
(镀锡)	(mm)	(螺孔)	(焊脚)	100mmx20mm	(产品号)	(黄铜)
(镀锡)	(mm)	(螺孔)	(焊脚)	100mmx20mm	(产品号)	(紫铜)

		GENRL TOLERANCE		制图	07		深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO., LTD			
		DIM	TOL	审核						
		5 or more	±0.35	批准			产品名称	PCB 焊接端子 厚度1.5 插板 铆垫片	版本	A
		2~5	±0.25	APPROVAL			TITLE	M5 6焊脚 14.5x14.5x10.5mm	REV.	
		0~2	±0.15	比例			产品料号	HC-RG1556-1414-D706-07	单位	mm
		Angle	±3.0°	SCALE			PART NO.		页次	1/1
序号	变更内容	日期	投影				MATERIAL		SHEET	
No.	MODIFY CONTENT	MODIFY DATE								