



NOTES:

备注

1. Brass or purple copper, Bright tin-plating  
黄铜或紫铜, 镀亮锡
2. Wire screw hole M4  
压线螺孔M4
3. Current Rating: 60A  
额定电流:60A
4. There shall be no defects such as pin deformation and burrs.  
不得有脚变形, 毛刺等缺陷
5. Unmarked dimensions refer to tolerances  
未标注的尺寸参考公差

Ordering Information

HC - \* \*\* \* - \*\*\*\* - \* \*\* \* - 07

Type	Thickness	Screw Thread	Welding Feet	Series	Pin/P	Product No.	Material
Pin (焊脚)	0.8±0.1mm	M3 (螺牙)	2个	1620#16x20mm	Pin	产品序号	镀锡铜
Nut (螺母)	1.0±0.1mm	M4 (螺牙)	2个	.....	Pin		镀锡铜
Gasket (垫片)	1.5±0.1mm	M4 (螺牙)	4个		Dip		镀锡铜
Gasket (垫片)	2.0±0.1mm	M6 (螺牙)	6个				镀锡铜
Gasket (垫片)	2.5±0.1mm	M6 (螺牙)	8个				镀锡铜
Gasket (垫片)	3.0±0.1mm		.....				镀锡铜

			GENREL TOLERANCE	制图	07	深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO.,LTD			
			DIM TOL	审核		产品名称	PCB 焊接端子 厚度1.0 插板 铆垫片	版本	A
			5 or more ±0.35	CHECK		TITLE	M4 4焊脚 10x8x13.2mm	REV.	
			2~5 ±0.25	批准		产品料号	HC-RG1044-1008-D313-07	单位	mm
			0~2 ±0.15	APPROVAL		PART NO.		页次	1/1
1	初版发行		Angle ±3.0°	SCALE		材料		SHEET	
序号	变更内容	日期	投影	Projection		MATERIAL			
No.	MODIFY CONTENT	MODIFY DATE							