



PCB 参考安装方式

NOTES:

- 备注
1. Copper, Bright tin plated
黄铜, 镀亮镍
 2. Wire screw hole M4
压线螺孔M4
 3. Current Rating: 45A
额定电流:45A
 4. There shall be no defects such as pin deformation and burrs.
不得有脚变形, 毛刺等缺陷
 5. Unmarked dimensions refer to tolerances
未标注的尺寸参考公差

Ordering Information

HC - * ** * - **** - * ** * - 07

Type	Thickness	Screw Thread	Welding Feet	Series	Welding	Product No.	Material
插脚 (插脚)	0.8mm 1.0mm 1.2mm 1.5mm 2.0mm 2.5mm 3.0mm	M4 (螺牙) M4 (螺牙) M4 (螺牙) M4 (螺牙) M4 (螺牙) M4 (螺牙) M4 (螺牙)	2个 2个 4个 6个 8个	1608-1620mm	SMD Dip	产品序号	默认: Copper (黄铜) 镀: Red Copper (镀铜)

		GENERAL TOLERANCE	制图	07	深圳市华灿天禄电子有限公司 ShenzhenhuacantianlueLECTRONICS CO., LTD			
		DIM TOL	审核					
		5 or more ±0.35	批准		产品名称	PCB 焊接端子 厚度0.8 插板 铆垫片	版本	A
		2~5 ±0.25	比例		TITLE	M4 4焊脚 8x8x13.2mm	REV.	
		0~2 ±0.15	投影		产品料号	HC-RG0844-0808-D205-07	单位	mm
序号	变更内容	日期	投影		MATERIAL		页次	1/1
No.	MODIFY CONTENT	MODIFY DATE					SHEET	