



NOTES:
备注

- 1.Brass or purple copper,Bright tin-plating
黄铜或紫铜，镀亮锡
- 2.Wire screw hole M6
压线螺孔M6
- 3.Current Rating: 180A
额定电流:180A
- 4.There shall be no defects such as pin deformation and burrs.
不得有脚变形，毛刺等缺陷
- 5.Unmarked dimensions refer to tolerances
未标注的尺寸参考公差

Ordering Information

HC - * * * * - * * * * - * * * * - 07

Type	Thickness	Screw Thread	Welding Feet	Series	Pin	Product No.	Material
类型	厚度	螺孔	焊脚	系列	插针	产品序号	材料
HC-RG-2068-1620-D901-07	2.0mm	M6	16x20mm	1620	8		铜

			GENEAL TOLERANCE	制图	07		
			DIM TOL	审核			
			5 or more ±0.35	批准			
			2~5 ±0.25	比例			
			0~2 ±0.15	SCALE			
			Angle ±3.0°	投影			
1	初版发行						
序号	变更内容	日期			产品名称	PCB 焊接端子 厚度2.0 插板 铆垫片	版本
No.	MODIFY CONTENT	MODIFY DATE			TITLE	M6 8焊脚 16x20x14mm	REV.
					产品料号	HC-RG2068-1620-D901-07	单位
					PART NO.		UNITS
					材料		页次
					MATERIAL		SHEET
							1/1

深圳市华灿天禄电子有限公司
ShenzhenhuacantianluELECTRONICS CO.,LTD