



NOTES:

备注

1. Brass or purple copper, Bright tin-plating
黄铜或者紫铜, 镀亮锡
2. Wire screw hole M5
压线螺孔M5
3. Current Rating: 80A
额定电流: 80A
4. There shall be no defects such as pin deformation and burrs.
不得有脚变形, 毛刺等缺陷
5. Unmarked dimensions refer to tolerances
未标注的尺寸参考公差

Ordering Information

HC - * * * * - * * * * - * * * * - 07

Type	Thickness	Screw Thread	Welding Feet	Series	Product No.	Material
插板 (插脚)	0.6mm	M5	1.5	100	HC-RG1554-1212-D701-07	紫铜
螺母	0.6mm	M5	1.5	100	HC-RG1554-1212-D701-07	紫铜
螺柱	0.6mm	M5	1.5	100	HC-RG1554-1212-D701-07	紫铜
螺帽	0.6mm	M5	1.5	100	HC-RG1554-1212-D701-07	紫铜
螺柱	0.6mm	M5	1.5	100	HC-RG1554-1212-D701-07	紫铜
螺帽	0.6mm	M5	1.5	100	HC-RG1554-1212-D701-07	紫铜

PCB 参考安装方式

		GENEAL TOLERANCE		制图	07		
		DIM	TOL	审核			
		5 or more	±0.35	批准	产品名称 PCB 焊接端子 厚度1.5 插板 铆垫片		
		2~5	±0.25	比例	M5 4焊脚 12x12x10.5mm		
		0~2	±0.15	投影	产品料号	HC-RG1554-1212-D701-07	版本
序号	变更内容	日期	角度	Projection	PART NO.		REV.
No.	MODIFY CONTENT	MODIFY DATE	±3.0°		MATERIAL		UNITS
							mm
							页次
							SHEET
							1/1

深圳市华灿天禄电子有限公司
ShenzhenhuacantianlueELECTRONICS CO., LTD