



NOTES:

- 备注
1. Brass or purple copper, Bright tin-plating
黄铜或紫铜, 镀亮锡
 2. Wire screw hole M5
压线螺孔M5
 3. Current Rating: 70A
额定电流:70A
 4. There shall be no defects such as pin deformation and burrs.
不得有脚变形, 毛刺等缺陷
 5. Unmarked dimensions refer to tolerances
未标注的尺寸参考公差

Ordering Information

HC - * ** * - **** - * ** * - 07

Type	Thickness	Screw Thread	Welding Foot	Series	Mount	Product No.	Material
Pin (插针)	0.8mm	M5 (螺牙)	2mm	0102010mm	0102010mm	产品序号	Brass (黄铜)
Wire screw hole (压线螺孔)	1.2mm	M5 (螺牙)	2mm	0102010mm	0102010mm	产品序号	Brass (黄铜)
Wire screw hole (压线螺孔)	1.2mm	M5 (螺牙)	2mm	0102010mm	0102010mm	产品序号	Brass (黄铜)
Wire screw hole (压线螺孔)	1.2mm	M5 (螺牙)	2mm	0102010mm	0102010mm	产品序号	Brass (黄铜)
Wire screw hole (压线螺孔)	1.2mm	M5 (螺牙)	2mm	0102010mm	0102010mm	产品序号	Brass (黄铜)

		GENRL TOLERANCE		制图	07		
		DIM	TOL	审核			
		5 or more	±0.35	批准	产品名称 PCB 焊接端子 厚度1.2 贴片 抽牙 M5 4焊脚 40x10x7.9mm		
		2~5	±0.25	比例	版本 REV. A		
		0~2	±0.15	投影	产品料号 PART NO. HC-M1254-4010-S526-07		
1	初版发行	日期	±3.0°	材料	单位 UNITS mm		
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE		材料 MATERIAL	页次 SHEET 1/1		

深圳市华灿天禄电子有限公司
ShenzhenhuacantianlueELECTRONICS CO., LTD