



NOTES:

- 备注
1. Brass or purple copper, Bright tin-plating
黄铜或紫铜, 镀亮锡
 2. Wire screw hole M5
压线螺孔M5
 3. Current Rating: 100A
额定电流:100A
 4. There shall be no defects such as pin deformation and burrs.
不得有脚变形, 毛刺等缺陷
 5. Unmarked dimensions refer to tolerances
未标注的尺寸参考公差

Ordering Information

HC - * * * * - * * * * - 07

Type	Thickness	Screw Thread	Welding Feet	Series	Product No.	Material
插脚 (插脚)	0.8mm	M5 (螺牙)	100° (焊脚)	18x14x18mm	HC-RG1554-1814-D715-07	黄铜 (黄铜)
螺母 (螺母)	0.8mm	M5 (螺牙)	100° (焊脚)	18x14x18mm	HC-RG1554-1814-D715-07	黄铜 (黄铜)
焊脚 (焊脚)	0.8mm	M5 (螺牙)	100° (焊脚)	18x14x18mm	HC-RG1554-1814-D715-07	黄铜 (黄铜)
焊脚 (焊脚)	0.8mm	M5 (螺牙)	100° (焊脚)	18x14x18mm	HC-RG1554-1814-D715-07	黄铜 (黄铜)

		GENERAL TOLERANCE	制图	07	深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO., LTD			
		DIM TOL	审核					
		5 or more ±0.35	批准		产品名称	PCB 焊接端子 厚度1.5 插板 铜垫片	版本	A
		2~5 ±0.25	比例		TITLE	M5 4焊脚 18x14x18mm	REV.	
		0~2 ±0.15	投影		产品料号	HC-RG1554-1814-D715-07	单位	mm
1	初版发行	日期	投影		PART NO.		页次	1/1
序号	变更内容	日期	投影		MATERIAL		SHEET	
No.	MODIFY CONTENT	MODIFY DATE	Projection					