



NOTES:
备注

1. Brass or purple copper, Bright tin-plating
黄铜或紫铜, 镀亮锡
2. Wire screw hole M4
压线螺孔M4
3. Current Rating: 60A
额定电流:60A
4. There shall be no defects such as pin deformation and burrs.
不得有脚变形, 毛刺等缺陷
5. Unmarked dimensions refer to tolerances
未标注的尺寸参考公差

Ordering Information

HC - * ** * - **** - * ** * - 07

Type	Thickness	Screw Thread	Welding Feet	Series	Welding Feet	Product No.	Material
Welding Feet (焊脚)	0.5~1.0mm	M3 (螺牙)	2个	1620=16x20mm	Welding Feet (焊脚)	产品序号	Welding Feet (焊脚)
Welding Nut (焊螺母)	1.0~1.2mm	M4 (螺牙)	2个	Welding Nut (焊螺母)	Welding Nut (焊螺母)
Welding Gasket (焊垫片)	1.5~1.8mm	M6 (螺牙)	4个	Welding Gasket (焊垫片)	Welding Gasket (焊垫片)
	2.0~2.2mm	M6 (螺牙)	6个			
	2.5~2.8mm	M6 (螺牙)	8个			
	3.0~3.2mm	M6 (螺牙)			

			GENREL TOLERANCE	制图	07			深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO.,LTD		
			DIM TOL	审核						
			5 or more ±0.35	批准				产品名称 PCB 焊接端子 厚度1.0 插板 铆垫片		
			2~5 ±0.25	APPROVAL				M4 4焊脚 10x8x10.2mm		
			0~2 ±0.15	比例				版本 REV. A		
			Angle ±3.0°	SCALE				产品料号 HC-RG1044-1008-D311-07		
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE		投影				单位 UNITS mm		
					材料 MATERIAL			页次 SHEET 1/1		