



- NOTES:
备注
1. Brass or purple copper, Bright tin-plating
黄铜或紫铜, 镀亮锡
 2. Wire screw hole M5
压线螺孔M5
 3. Current Rating: 100A
额定电流:100A
 4. There shall be no defects such as pin deformation and burrs.
不得有脚变形, 毛刺等缺陷
 5. Unmarked dimensions refer to tolerances
未标注的尺寸参考公差

Ordering Information

HC - * * * * - * * * * - 07

Type	Thickness	Screw Thread	Welding Feet	Series	Part No.	Product No.	Material
(Type)	(0.5, 0.8)	(M2, M2.5)	(焊脚)	(0100#0.30mm)	(Part No.)	(Product No.)	(Material)
(Type)	(1.0, 1.5)	(M3, M3.5)	(焊脚)	(1620#1.6x20mm)	(Part No.)	(Product No.)	(Material)
(Type)	(2.0, 2.5)	(M4, M4.5)	(焊脚)	(.....)	(Part No.)	(Product No.)	(Material)

PCB 参考安装方式

		GENEAL TOLERANCE		制图	07		
		DIM	TOL	审核			
		5 or more	±0.35	批准	产品名称 PCB 焊接端子 厚度1.5 插板 铆垫片		
		2~5	±0.25	APPROVAL	M5 4焊脚 16x20x19mm		
		0~2	±0.15	比例	产品料号	HC-RG1554-1620-D721-07	版本
		Angle	±3.0°	SCALE	PART NO.		REV.
序号	变更内容	日期		投影	材料		单位
No.	MODIFY CONTENT	MODIFY DATE			MATERIAL		UNITS
							页次
							SHEET
							1/1

深圳市华灿天禄电子有限公司
ShenzhenhuacantianluELECTRONICS CO., LTD